

Certificate
2610702 (1)



Issued 02/10/2026
Valid until 02/04/2027

Kiwa UK Regulation 4 (KUKreg4) Approval

Kiwa hereby declares that legitimate confidence exists in the products specified and model number(s) listed in the Appendix for:

Electrolux Professional S.p.A.

meets the requirements as described in the
Evaluation Guideline – Kiwa UK – EG004 (Issue 7) – Regulation 4(1)(a)

Which verifies the requirements of reference standard(s):

Regulation 4(1)(a) of the Water Supply (Water Fittings) Regulations 1999 England & Wales: 2009 Northern Ireland and 2014 Byelaws Scotland.

This certificate has been issued in accordance with the Kiwa regulations for product certification and is only valid in combination with the appendix.

David Jay
Business Unit Manager- Authorised
Signatory Kiwa Limited (Watertec)

This certificate relates to products intended to be used in the UK only. For other countries, other (National) requirements will apply.

Disclosure of the certificate is permitted in full.

To check the validity of a certificate, scan the QR code or go to <https://www.kiwa.com/gb/en-gb/about-kiwa/water-products/>



Appendix

The following products belong to this certificate

PRODUCT DESCRIPTION myPRO range of commercial washing machines with flow controlled by solenoid valves and discharged via a type 'AB' airgap (verified by test) suitable for backflow protection against fluid category 5. ATS3 – Without Production Surveillance.
MODEL(S) WE170P, WE170PP, WE170V, WE170VP, WE2-9, WE2-9PS This machine can have two different drain system. - WE170V, WE170VP, WE2-9 with Drain valve. - WE170P, WE170PP, WE2-9PS Pump drain.
SIZE: ¾" BSP captive nut.
SCOPE: Manufacturer recommended maximum working pressure 8 Bar & maximum operating temperature 55°C. Hygienic Purposes: Non-metallic materials suitable for continuous use up to 55°C.
MARKING Electrolux on soap tray. Electrolux, model number and serial number on back of body.
MATERIALS Non-metallic materials assessed (BS6920) to backflow prevention device.
BACKFLOW PROTECTION NOTES A compliant double check valve shall be fitted upstream of the flexible hose supplied. Cleaning agents used via the external liquid connection must be no greater than a fluid category 3 risk. The outlet of the air gap weir must not be restricted when installed.
ADDITIONAL NOTES All water contact & exposed components satisfy opacity requirements.

Extra Notes